



US009636808B2

(12) **United States Patent**
Ho

(10) **Patent No.:** **US 9,636,808 B2**
(45) **Date of Patent:** **May 2, 2017**

(54) **IMPACT DEVICE OF PNEUMATIC TOOL**

(71) Applicant: **Chuan-Cheng Ho**, Taichung (TW)

(72) Inventor: **Chuan-Cheng Ho**, Taichung (TW)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 438 days.

(21) Appl. No.: **14/530,271**

(22) Filed: **Oct. 31, 2014**

(65) **Prior Publication Data**

US 2015/0114674 A1 Apr. 30, 2015

(30) **Foreign Application Priority Data**

Oct. 31, 2013 (TW) 102139619 A

(51) **Int. Cl.**

B25B 21/02 (2006.01)
B25B 19/00 (2006.01)
B25B 23/145 (2006.01)

(52) **U.S. Cl.**

CPC **B25B 19/00** (2013.01); **B25B 21/02** (2013.01); **B25B 21/026** (2013.01); **B25B 23/1453** (2013.01)

(58) **Field of Classification Search**

CPC B25B 21/02; B25B 21/026; B25B 19/00; B25B 23/1453
USPC 173/93, 93.5, 93.6, 104, 128, 206, 218, 173/168; 464/25, 26, 28
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,228,486 A * 1/1966 Kaman B25B 21/02
173/93.6
3,789,934 A * 2/1974 Schoeps B25B 21/026
173/93.5

4,533,337 A * 8/1985 Schoeps B25B 21/026
173/93
4,557,337 A * 12/1985 Shibata B25B 21/026
173/93
4,683,961 A * 8/1987 Schoeps B25B 21/02
173/93
4,735,595 A * 4/1988 Schoeps B25B 21/02
173/93
4,767,379 A * 8/1988 Schoeps B25B 21/02
173/93.5
4,836,296 A * 6/1989 Biek B25B 23/1453
173/93.5
5,622,230 A * 4/1997 Giardino B25B 21/02
173/93

(Continued)

Primary Examiner — Scott A. Smith

(74) *Attorney, Agent, or Firm* — Muncy, Geissler, Olds & Lowe, P.C.

(57) **ABSTRACT**

An impact device includes a transmission shaft, an impact cylinder, two first impact pins and a first ring. The transmission shaft has an impacted section disposed in the impact cylinder, an extending section extending along an axis, a first protrusion extending toward a first radial direction, and two first concave surfaces located at the first protrusion. The impact cylinder has two elongated protrusions and two first radial holes separated by the elongated protrusions. The first impact pins are received in the first radial holes in parallel to the axis and abutable against the first concave surfaces. The first ring is sleeved onto the impact cylinder and the first impact pins and has a first narrow groove in which one elongated protrusion is located, and a first wide groove in which the other elongated protrusion is movably located. The impact device has sufficient torque output and long lifetime.

5 Claims, 12 Drawing Sheets

